

# DECO PRIMER BASE

## Coarse grained clinging

### DESCRIPTION

Isoplam® Deco Primer Base is a coarse grained clinging that is used to improve the adhesion of Isoplam® Plam Stone and Plam Rock on gypsum, lime-gypsum plaster and on concrete supports.

### TECHNICAL FEATURES

Grain size: less than 0,50 mm.  
Dosage: 8-10 mq/Lt per coat.

### SUPPORT PREPARATION AND APPLICATION

The wall must be clean, without dust, dirt, saline efflorescences, etc. Possible oil, grease, wax stains must be removed before the application. Do not apply on friable surfaces. Deco Primer Base must be diluted with max 30% of water and applied by roller or brush. The subsequent application of products must be made after its drying.

### CAUTION

Deco Primer Base must be applied on dried surfaces with less than 75% humidity and with temperatures between + 5° C and + 35 °C.

### PACKAGE AND STORAGE

Deco Primer Base is supplied in buckets of 5 Lt.  
In the original and sealed packages, stored in a closed and protected place at temperatures between 5 and 35 ° C, it remains unchanged for at least one year from the date shown on the package (the batch number indicates, year after week, the sequence).

### SAFETY

Isoplam® Deco Primer Base is intended for professional use only.  
Consult the Safety Data Sheet before use.

**IMPORTANT: The product Deco Primer Base is intended for the use as indicated above. Adding any other product will impair the final result. All information contained herein is based on the best practical experiences and laboratory research. It is the customer's responsibility to determine whether the product is suitable for the intended application. The manufacturer declines all responsibility on the results due to incorrect application of its products. The product shall always be tested on a small area before full scale application. This data sheet replaces all previous data sheets. ISOPLAM reserves the right to change the data on the data sheet at any time. Deco Primer Base is intended for professional use only. ISOPLAM provides frequent and on demand trainings for its customers. The use of ISOPLAM products without receiving the proper certification will be at the customer's own risk.**