

# PLAM RELE

## Powder release agent for stamped floor

### DESCRIPTION

Isoplam® Plam Rele is a pre-mixture of micronized powders, non-stick, water repellents, coloring release agents. It is a product that is distributed on a surface previously treated with Isoplam® Plam Hardening for the creation of stamped decorative concrete floors.

Its formulation allows the easy detachment of the stamps, giving also colored shades to floorings and highlighting the texture of the desired mold.

### FIELDS OF USE

Isoplam® Plam Rele is used in all the environments where you can create stamped concrete.

### APPLICATION

Isoplam® Plam Rele will be sprinkled on the surface using the appropriate brush on Isoplam® Plam Hardening, which has been previously incorporated in the concrete and carefully smoothed. It is recommended to apply a thin layer of Isoplam® Plam Rele also on the stamps, if these are new or never been used.

After distributing Isoplam® Plam Rele on the surface, place Isoplam® molds and beat them uniformly with the special Isoplam® anti-vibration rubber tamper on the fresh concrete, in order to stamp the desired design on the surface.

After about 48 hours (depending on the season: during cold periods even after 4 days) gently remove, but not completely, Isoplam® Plam Rele with a pressure washer.

To avoid excessive dispersion of dust in the air during the cleaning, we recommend to apply Isoplam® Plam Dust Cleaner. It is not recommended the application of Isoplam® Plam Rele in case of strong winds that would increase air dispersion and consumption.

Wash Isoplam® molds with Isoplam® Plam Stamp Cleaner and water.

### CONSUMPTION

150-160 gr/m<sup>2</sup>.

### PACKAGING AND COLORS

Isoplam® Plam Rele is supplied in plastic vases of 13,6 kg in 18 colors, as indicated in the Isoplam® Color Chart.

### STORAGE

Store at temperatures between +5°C and +35°C.

If properly stored, it keeps for 12 months in its original sealed packages.

#### ISOPLAM S.R.L.

Via E. Mattei, 4 – Z. I. Maser (TV) – Italia  
IDENTIFICAZIONE ISO 9001:2015

Tel. (+39) 0423 925023 Fax (+39) 0423 926119  
Rev. 27/07/2016

www.isoplam.it



## SAFETY

Avoid breathing the dust and direct contact.  
Use dust masks and gloves.  
Consult the Safety Data Sheet before use.  
The product is intended for professional use only.

Each individual work must be completed using a single production lot, otherwise Isoplam Srl is not responsible for differences in color.

### IMPORTANT:

The product **PLAM RELE** is intended for the use as indicated above. Adding any other product will impair the final result. All information contained herein is based on the best practical experiences and laboratory research. It is the customer's responsibility to determine whether the product is suitable for the intended application. The manufacturer declines all responsibility on the results due to incorrect application of its products. The product shall always be tested on a small area before full scale application. This data sheet replaces all previous data sheets. ISOPLAM reserves the right to change the data on the data sheet at any time. **PLAM RELE** is intended for professional use only. ISOPLAM provides frequent and on demand trainings for its customers. The use of ISOPLAM products without receiving the proper certification will be at the customer's own risk.

### ISOPLAM S.R.L.

Via E. Mattei, 4 – Z. I. Maser (TV) – Italia  
*IDENTIFICAZIONE ISO 9001:2015*

Tel. (+39) 0423 925023 Fax (+39) 0423 926119  
Rev. 27/07/2016

[www.isoplam.it](http://www.isoplam.it)